



U625/U725 SERIES: High quality, 25 gauge 2-inch thick insulated steel door. This product sets the standard by which all other doors of this type are measured; it is undeniably the best in its class.

Specifications:

Sections: Are 2 inches thick in 21 and 18-inch section heights. Each section is manufactured from 25-gauge hot dipped galvanized steel on the face skin and 26 ga. on the backskin. Both of the steel skins are pre-painted white or almond with a ten coat rust protection system and rotary embossed with a woodgrain texture. Traditional definition and Bead Board raised panels are pressed into the steel face skin in .125 increments and obtain a depth of .375" which is exclusive among garage doors. The steel skins are laminated to a CFC-free polystyrene core delivering an R-value up to 9.0. Tongue and groove meeting rails ensure a weather tight fit at the section joints. Bottom sections are fitted with a full-length reinforced aluminum bottom retainer that is mechanically fastened and bonded to the section with structural adhesive for added strength and it supports a replaceable UV protected grooved weather seal for further weather protection.

H-2 Hardware And Track:

Hinges are hot dipped galvanized, 14/16-gauge wide body end roller hinges and 16-gauge interior hinges. Rollers are 2-inch black nylon or optional white nylon, galvanized torsion tube; self-locking fasteners, pre-painted torsion springs, and optional inside lock.

Models:

U6251 SP	25 gauge door 191/4" x 133/4" Traditional Definition (SP)
U6252 LP	25 gauge door 42" x 133/4" Traditional Definition (LP)
U6250 FL	25 gauge door Flush woodgrain No Definition (FL)
U725	25 gauge door 18" x 133/4" Traditional Carriage Bead Board

Widths & Heights:

Width:	8', 9', 10', 15', 16', 18'
Height:	6'3", 6'6", 6'9", 7', 7'6", 7'9", 8'

Up Grade Options:

Glass Designs: Various Designs- See Brochures

Insulation: CFC free polystyrene insulation with a 26 gauge back cover laminated to the face of the door with an R-factor of 9.0.

Hardware: H-3 Optional hardware includes 14-gauge commercial hinges throughout. Commercial top fixtures and heavy-duty bottom fixtures, 10 ball white Nylon rollers, double lift handles, inside slide lock, back-hang fasteners, pre-painted springs, galvanized torsion tube, .051 vertical track, and .060 horizontal track.